



700 SERIES

GAS RANGE, CG-720

1120101200

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	35,00
Gross Weight	Kg	43,00
Volume packed	m3	0,17

GAS RANGE, CG-720

Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 2 x 4000 kcal/h
 Dimensions of the grill: 347x310 mm.
 Total power: 8.000 Kcal/h. (9.3 kW).
 Dimensions: 350 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	9,30
	Kcal/h	7.998,00
LPG		
Consumption (kg/h)		0,66
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		0,83
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)		0,00
Pressure (Kg/cm2)		

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	310	494	0	R.3/4"G





700 SERIES

GAS RANGE, CG-720 H

1120101213

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	35,00
Gross Weight	Kg	43,00
Volume packed	m3	0,17

GAS RANGE, CG-720 H

Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 2 x 8000 kcal/h
 Dimensions of the grill: 347x310 mm.
 Total power: 16,000 Kcal/h. (18.6 kW).
 Dimensions: 350 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	18,60
	Kcal/h	16.000,00
LPG		
Consumption (kg/h)		1,48
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		1,90
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	310	494	0	R.3/4"G



700 SERIES

GAS RANGE, CG-740



1120101300

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	61,00
Gross Weight	Kg	75,00
Volume packed	m3	0,32

GAS RANGE, CG-740

Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 1 x 6000 + 3 x 4000 kcal/h
 Dimensions of the grill: 347x310 mm.
 Total power: 18.000 Kcal/h. (20.93 kW).
 Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	20,93
	Kcal/h	17.999,80
LPG		
Consumption (kg/h)		1,56
Pressure (g/cm ²)		37,00
Natural Gas		
Consumption (m ³ /h)		2,09
Pressure (g/cm ²)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	0	R.3/4"G



700 SERIES

GAS RANGE, CG-740 H



1120101313

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	61,00
Gross Weight	Kg	75,00
Volume packed	m3	0,32

GAS RANGE, CG-740 H

Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 4 x 8000 kcal/h
 Dimensions of the grill: 347x310 mm.
 Total power: 32,000 Kcal/h. (37.21 kW).
 Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	37,21
	Kcal/h	32.000,00
LPG		
Consumption (kg/h)		3,00
Pressure (g/cm ²)		37,00
Natural Gas		
Consumption (m ³ /h)		3,85
Pressure (g/cm ²)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	0	R.3/4"G





700 SERIES

GAS RANGE, CG-741

1120101400

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	134,00
Gross Weight	Kg	152,00
Volume packed	m3	0,66

GAS RANGE, CG-741

Made of stainless steel AISI-304 (18/10).

Open hobs with safety valve and thermocouples.

Pilots for ignition. Cast iron gratings and burners.

Burners: 1 x 6000 + 3 x 4000 kcal/h

Dimensions of the grill: 347x310 mm.

2/1 GN oven with burner in stainless steel. Pilot and thermocouple. Thermostatic control (130 °C – 350 °C).

Oven burner: 6000 kcal/h.

Total power: 24.000 Kcal/h. (27.9 kW).

Dimensions: 700 x 750 x 850 mm.

Electricity

No

Gas

Gas Power	KW	27,90
	Kcal/h	23.994,00
LPG		
Consumption (kg/h)		2,19
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		2,78
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	105	R.3/4"G





700 SERIES

GAS RANGE, CG-741 H

1120101413

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	134,00
Gross Weight	Kg	152,00
Volume packed	m3	0,66

GAS RANGE, CG-741 H

Made of stainless steel AISI-304 (18/10).

Open hobs with safety valve and thermocouples.

Pilots for ignition. Cast iron gratings and burners.

Burners: 4 x 8000 kcal/h

Dimensions of the grill: 347x310 mm.

2/1 GN oven with burner in stainless steel. Pilot and thermocouple. Thermostatic control (130 °C - 350 °C).

Oven burner: 6000 kcal/h.

Total power: 38,000 Kcal/h. (44.2 kW).

Dimensions: 700 x 750 x 850 mm

Electricity

No

Gas

Gas Power	KW	44,19
	Kcal/h	38.000,00
LPG		
Consumption (kg/h)		3,15
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		4,23
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	105	R.3/4"G





700 SERIES

GAS RANGE, CG-761

1120101500

Dimensions and Weights

Length	mm	1.050,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	155,00
Gross Weight	Kg	196,50
Volume packed	m3	1,02

GAS RANGE, CG-761

Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 2 x 6000 + 4 x 4000 kcal/h
 Dimensions of the grill: 347x310 mm.
 2/1 GN oven with burner in stainless steel. Pilot and thermocouple. Thermostatic control (130 °C – 350 °C).
 Oven burner: 6000 kcal/h.
 Auxiliary neutral cabinet.
 Total power: 34.000 Kcal/h. (39.53 kW).
 Dimensions: 1050 x 750 x 850 mm.

Electricity

No

Gas

Gas Power	KW	39,53
	Kcal/h	33.995,80
LPG		
Consumption (kg/h)		3,10
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		3,93
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	1.010	494	105	R.3/4"G





700 SERIES

GAS RANGE, CG-761 H

1120101513

Dimensions and Weights

Length	mm	1.050,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	155,00
Gross Weight	Kg	196,50
Volume packed	m3	1,02

GAS RANGE, CG-761 H

Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 6 x 8000 kcal/h
 Dimensions of the grill: 347x310 mm.
 2/1 GN oven with burner in stainless steel. Pilot and thermocouple. Thermostatic control (130 °C - 350 °C).
 Oven burner: 6000 kcal/h.
 Auxiliary neutral cabinet.
 Total power: 54.000 Kcal/h. (62.8 kW).
 Dimensions: 1050 x 750 x 850 mm.

Electricity

No

Gas

Gas Power	KW	62,79
	Kcal/h	54.000,00
LPG		
Consumption (kg/h)		4,30
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		5,50
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)		0,00
Pressure (Kg/cm2)		

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	1.010	494	105	R.3/4"G





700 SERIES

GAS RANGE, CGB-761

1120100600

Dimensions and Weights

Length	mm	1.050,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	155,00
Gross Weight	Kg	196,50
Volume packed	m3	1,02

GAS RANGE, CGB-761

Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 2 x 6000 + 4 x 4000 kcal/h
 Dimensions of the grill: 347x310 mm.
 UK style oven with temperature gradient from top to bottom of oven.
 Pilot and thermocouple. Thermostatic control (130 °C – 350 °C).
 Double side door.
 Oven burner: 6300 kcal/h. (7.3 kW).
 Total power: 32.630 Kcal/h. (37.94 kW).
 Dimensions: 1050 x 750 x 850 mm.

Electricity

No

Gas

Gas Power	KW	37,94
	Kcal/h	32.628,40
LPG		
Consumption (kg/h)		3,10
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		3,93
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	1.010	494	105	R.3/4"G





700 SERIES

GAS RANGE, CGB-761 R

1120100603

Dimensions and Weights

Length	mm	1.050,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	155,00
Gross Weight	Kg	196,50
Volume packed	m3	1,02

GAS RANGE, CGB-761 R

With castors.
 Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 2 x 6000 + 4 x 4000 kcal/h
 Dimensions of the grill: 347x310 mm.
 UK style oven with temperature gradient from top to bottom of oven.
 Pilot and thermocouple. Thermostatic control (130 °C - 350 °C).
 Double side door.
 Oven burner: 6300 kcal/h. (7.3 kW).
 Total power: 32.630 Kcal/h. (37.94 kW).
 Dimensions: 1050 x 750 x 850 mm.

Electricity

No

Gas

Gas Power	KW	37,94
	Kcal/h	32.628,40
LPG		
Consumption (kg/h)		3,10
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		3,93
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	1.010	494	105	R.3/4"G





700 SERIES

GAS RANGE, CGB-761 RH

1120100606

Dimensions and Weights

Length	mm	1.050,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	155,00
Gross Weight	Kg	196,50
Volume packed	m3	0,97

GAS RANGE, CGB-761 RH

With castors.
 Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 6 x 8000 kcal/h
 Dimensions of the grill: 347x310 mm.
 UK style oven with temperature gradient from top to bottom of oven.
 Pilot and thermocouple. Thermostatic control (130 °C - 350 °C).
 Double side door.
 Oven burner: 6300 kcal/h. (7.3 kW).
 Total power: 54,300 Kcal/h. (63.14 kW).
 Dimensions: 1050 x 750 x 850 mm.

Electricity

No

Gas

Gas Power	KW	63,14
	Kcal/h	54.300,00
LPG		
Consumption (kg/h)		4,30
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		5,50
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	1.010	494	105	R.3/4"G





700 SERIES

GAS RANGE, CGB-761 H

1120100608

Dimensions and Weights

Length	mm	1.050,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	155,00
Gross Weight	Kg	196,50
Volume packed	m3	1,02

GAS RANGE, CGB-761 H

Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 6 x 8,000 kcal/h
 Dimensions of the grill: 347x310 mm.
 UK style oven with temperature gradient from top to bottom of oven.
 Pilot and thermocouple. Thermostatic control (130 °C - 350 °C).
 Double side door.
 Oven burner: 6300 kcal/h. (7.3 kW).
 Total power: 54,300 Kcal/h. (63.14 kW).
 Dimensions: 1050 x 750 x 850 mm.

Electricity

No

Gas

Gas Power	KW	63,14
	Kcal/h	54.300,00
LPG		
Consumption (kg/h)		4,30
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		5,50
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	1.010	494	105	R.3/4"G





700 SERIES

GAS RANGE, CG-731 D

1120101740

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	129,00
Gross Weight	Kg	147,00
Volume packed	m3	0,67

GAS RANGE, CG-731 D

Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 1 x 6000 + 1 x 4000 kcal/h
 Dimensions of the grill: 347x310 mm.
 One solid top on the right side of the work-top, cast iron burner. Burner of 4000 kcal/h.
 Dimensions: 347x620 mm.
 Dimensions of the solid top plate: 695 x 310 mm.
 2/1 GN oven with burner in stainless steel.
 Pilot and thermocouple.
 Thermostatic control (130 °C - 350 °C).
 Oven burner: 6000 kcal/h.
 Total power: 20,000 Kcal/h. (23.3 kW).
 Dimensions: 700 x 750 x 850 mm.

Electricity

No

Gas

Gas Power	KW	23,30
	Kcal/h	20.038,00
LPG		
Consumption (kg/h)		2,19
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		2,78
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	105	R.3/4"G





700 SERIES

GAS RANGE, CG-731 I

1120101750

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	129,00
Gross Weight	Kg	147,00
Volume packed	m3	0,67

GAS RANGE, CG-731 I

Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 1 x 6000 + 1 x 4000 kcal/h
 Dimensions of the grill: 347x310 mm.
 One solid top on the left side of the work-top, cast iron burner. Burner of 4000 kcal/h.
 Dimensions: 347x620 mm.
 Dimensions of the solid top plate: 695 x 310 mm.
 2/1 GN oven with burner in stainless steel.
 Pilot and thermocouple.
 Thermostatic control (130 °C - 350 °C).
 Oven burner: 6000 kcal/h.
 Total power: 20,000 Kcal/h. (23.3 kW).
 Dimensions: 700 x 750 x 850 mm.

Electricity

No

Gas

Gas Power	KW	23,30
	Kcal/h	20.038,00
LPG		
Consumption (kg/h)		2,19
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		2,78
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	105	R.3/4"G



700 SERIES

GAS RANGE, CG-730 D



1120101760

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	61,00
Gross Weight	Kg	75,00
Volume packed	m3	0,32

GAS RANGE, CG-730 D

Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 1 x 6000 + 1 x 4000 kcal/h
 Dimensions of the grill: 347x310 mm.
 One solid top on the right side of the work-top, cast iron burner. Burner of 4000 kcal/h.
 Dimensions: 347x620 mm.
 Dimensions of the solid top plate: 695 x 310 mm.
 Total power: 14,000 Kcal/h. (16.3 kW).
 Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	16,30
	Kcal/h	14.018,00
LPG		
Consumption (kg/h)		1,56
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		2,09
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	0	R.3/4"G





700 SERIES

GAS RANGE, CG-730 I

1120101770

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	61,00
Gross Weight	Kg	75,00
Volume packed	m3	0,32

GAS RANGE, CG-730 I

Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 1 x 6000 + 1 x 4000 kcal/h
 Dimensions of the grill: 347x310 mm.
 One solid top on the left side of the work-top, cast iron burner. Burner of 4000 kcal/h.
 Dimensions: 347x620 mm.
 Dimensions of the solid top plate: 695 x 310 mm.
 Total power: 14,000 Kcal/h. (16.3 kW).
 Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	16,30
	Kcal/h	14.018,00
LPG		
Consumption (kg/h)		1,56
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		2,09
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	0	R.3/4"G





700 SERIES

GAS RANGE, CG-751

1120101780

Dimensions and Weights

Length	mm	1.050,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	160,00
Gross Weight	Kg	202,00
Volume packed	m3	0,97

GAS RANGE, CG-751

Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 2 x 6000 + 2 x 4000 kcal/h
 Dimensions of the grill: 347x310 mm.
 One solid top on the work-top, cast iron burner.
 Burner of 4000 kcal/h. Dimensions: 347x620 mm.
 2/1 GN oven with burner in stainless steel. Pilot and thermocouple. Thermostatic control (130 °C - 350 °C).
 Oven burner: 6000 kcal/h.
 Auxiliary neutral cabinet.
 Total power: 30.000 Kcal/h. (34.9 kW).
 Dimensions: 1050 x 750 x 850 mm.

Electricity

No

Gas

Gas Power	KW	34,90
	Kcal/h	30.014,00
LPG		
Consumption (kg/h)		3,10
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		3,93
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	1.010	494	105	R.3/4"G





700 SERIES

GAS RANGE, CG-750

1120101790

Dimensions and Weights

Length	mm	1.050,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	100,00
Gross Weight	Kg	115,00
Volume packed	m3	0,50

GAS RANGE, CG-750

Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 2 x 6000 + 2 x 4000 kcal/h
 Dimensions of the grill: 347x310 mm.
 One solid top on the work-top, cast iron burner.
 Burner of 4000 kcal/h. Dimensions: 347x620 mm.
 Total power: 24.000 Kcal/h. (27.9 kW).
 Dimensions: 1050 x 750 x 2900 mm.

Electricity

No

Gas

Gas Power	KW	27,90
	Kcal/h	23.994,00
LPG		
Consumption (kg/h)		2,10
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		2,80
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	1.010	494	0	R.3/4"G





700 SERIES

GAS RANGE, CG-710

1120101600

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	90,00
Gross Weight	Kg	109,00
Volume packed	m3	0,33

GAS RANGE, CG-710

Made of stainless steel AISI-304 (18/10).

Consists of: solid top on the work-top, cast iron burner with firebrick protection ensuring even heat distribution.

Dimensions of the solid top plate: 695 x 620 mm.

Total power: 8.000 Kcal/h. (9.3 kW).

Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	9,30
	Kcal/h	7.998,00
LPG		
Consumption (kg/h)		0,70
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		0,89
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	0	R.3/4"G





700 SERIES

GAS RANGE, CG-711

1120101700

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	165,00
Gross Weight	Kg	185,50
Volume packed	m3	0,66

GAS RANGE, CG-711

Made of stainless steel AISI-304 (18/10).

Consists of: solid top on the work-top, cast iron burner.

Burner of 8000 kcal/h.

Dimensions of the solid top plate: 695 x 620 mm.

2/1 GN oven with burner in stainless steel. Pilot and thermocouple. Thermostatic control (130 °C – 350 °C).

Oven burner: 6000 kcal/h.

Total power: 14.000 Kcal/h. (16.28 kW).

Dimensions: 700 x 750 x 850 mm.

Electricity

No

Gas

Gas Power	KW	16,28
	Kcal/h	14.000,80
LPG		
Consumption (kg/h)		1,24
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		1,58
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR330

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	105	R.3/4"G





700 SERIES

ELECTRIC RANGE, CE-720

1120101800

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	35,00
Gross Weight	Kg	43,00
Volume packed	m3	0,17

ELECTRIC RANGE, CE-720

Made of stainless steel AISI-304 (18/10).
 Cast iron hot- plates with shielded elements.
 6 settings switch. Indicator lights.
 Plates: 2 x 2600 W (Ø 220 mm).
 Total power: 5.2 kW.
 Dimensions: 350 x 750 x 290 mm.

Electricity

Electric Power	KW	5,20
Voltage 230V -1+N		2x4+T - 32 A
Voltage 230V - III		3x2,5+T - 25 A
Voltage 400V - III+N		4x1,5+T - 16 A

Gas


No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	321	335	0	





700 SERIES

ELECTRIC RANGE, CE-740

1120101900

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	63,00
Gross Weight	Kg	75,00
Volume packed	m3	0,32

ELECTRIC RANGE, CE-740

Made of stainless steel AISI-304 (18/10).
 Cast iron hot- plates with shielded elements.
 6 settings switch. Indicator lights.
 Plates: 3 x 2.600 W (Ø 220 mm)
 + 1 x 1.500 W (Ø 150 mm).
 Total power: 9.3 kW.
 Dimensions: 700 x 750 x 290 mm.

Electricity

Electric Power	KW	9,30
Voltage 230V -1+N		2x10+T - 50 A
Voltage 230V - III		3x4+T - 40 A
Voltage 400V - III+N		4x2,5+T - 32 A

Gas


No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	671	335	0	





700 SERIES

ELECTRIC RANGE, CE-741

1120102000

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	130,00
Gross Weight	Kg	152,00
Volume packed	m3	0,66

Electricity

Electric Power	KW	15,30
Voltage 230V -1+N		2x16+T - 80 A
Voltage 230V - III		3x10+T - 63 A
Voltage 400V - III+N		4x4+T - 40 A

Gas

No

ELECTRIC RANGE, CE-741


Made of stainless steel AISI-304 (18/10).
 Cast iron hot- plates with shielded elements.
 6 settings switch. Indicator lights.
 Plates: 3 x 2.600 W (Ø 220 mm)
 + 1 x 1.500 W (Ø 150 mm).
 2/1 GN oven with upper and lower heating elements.
 Selector switch for the elements.
 Thermostatic control (130 °C – 350 °C).
 Oven power: 6 kW.
 Total power : 15.3 kW.
 Dimensions: 700 x 750 x 850 mm.

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	32	515	150	





700 SERIES

GAS AND ELECTRIC RANGE, CGE-741

1120102100

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	134,00
Gross Weight	Kg	152,00
Volume packed	m3	0,66

Electricity

Electric Power	KW	6,00
Voltage 230V - I+N		2x4+T - 32 A
Voltage 230V - III		3x2,5+T - 20 A
Voltage 400V - III+N		4x1,5+T - 16 A

Gas

Gas Power	KW	20,93
	Kcal/h	17.999,80
LPG		
Consumption (kg/h)		1,56
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		2,09
Pressure (g/cm2)		18,00


Water

Consumption (lit/h)		0,00
Pressure (Kg/cm2)		

Certificate EQNET

99AR330

<u>Installation</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	32	515	150	
GAS	660	494	105	R.3/4"G



GAS AND ELECTRIC RANGE, CGE-741
 Made of stainless steel AISI-304 (18/10).
 Open hobs with safety valve and thermocouples.
 Pilots for ignition. Cast iron gratings and burners.
 Burners: 1 x 6000 + 3 x 4000 kcal/h
 Dimensions of the grill: 347x310 mm.
 2/1 GN oven with upper and lower heating elements.
 Selector switch for the elements.
 Thermostatic control (130 °C – 350 °C).
 Oven power: 6 kW.
 Total gas power: 18.000 kcal/h.(20.93 kW)
 Total electrical power: 6 kW.
 Dimensions: 700 x 750 x 850 mm.



700 SERIES

GAS FRY-TOP, FTG-710 L

1120201600

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	72,00
Gross Weight	Kg	85,00
Volume packed	m3	0,37

GAS FRY-TOP, FTG-710 L
 Made of stainless steel AISI-304 (18/10).
 Smooth hot-plate. Surface area: 43 dm².
 Burners in stainless steel with pilot.
 Thermostat control of the hot-plate temperature 120 C° -310 C°.
 Fat collector under the grill.
 Power: 12000 Kcal/h. (13.96 kW).
 Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas


Gas Power	KW	13,96
	Kcal/h	12.005,60
LPG		
Consumption (kg/h)		1,05
Pressure (g/cm ²)		37,00
Natural Gas		
Consumption (m ³ /h)		1,33
Pressure (g/cm ²)		18,00

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Certificate EQNET 99AR307

<u>Installation</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	57	R.3/4"G





700 SERIES

GAS FRY-TOP, FTG-710 R

1120201603

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	72,00
Gross Weight	Kg	85,00
Volume packed	m3	0,37

GAS FRY-TOP, FTG-710 R

Made of stainless steel AISI-304 (18/10).
 Ribbed hot-plate. Surface area: 43 dm².
 Burners in stainless steel with pilot.
 Thermostat control of the hot-plate temperature 120 C° -310 C°.
 Fat collector under the grill.
 Power: 12000 Kcal/h. (13.96 kW).
 Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	13,96
	Kcal/h	12.005,60
LPG		
Consumption (kg/h)		1,05
Pressure (g/cm ²)		37,00
Natural Gas		
Consumption (m ³ /h)		1,33
Pressure (g/cm ²)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Certificate EQNET

99AR307

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	57	R.3/4"G





700 SERIES

GAS FRY-TOP, FTG-710 L+R

1120201606

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	72,00
Gross Weight	Kg	85,00
Volume packed	m3	0,37

GAS FRY-TOP, FTG-710 L+R
 Made of stainless steel AISI-304 (18/10).
 ½ smooth – ½ ribbed hot-plate. Surface area: 43 dm².
 Burners in stainless steel with pilot.
 Thermostat control of the hot-plate temperature 120 C° -310 C°.
 Fat collector under the grill.
 Power: 12000 Kcal/h. (13.96 kW).
 Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas


Gas Power	KW	13,96
	Kcal/h	12.005,60
LPG		
Consumption (kg/h)		1,05
Pressure (g/cm ²)		37,00
Natural Gas		
Consumption (m ³ /h)		1,33
Pressure (g/cm ²)		18,00

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Certificate EQNET 99AR307

<u>Installation</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	57	R.3/4"G





700 SERIES

GAS FRY-TOP, FTG/C-710

1120201609

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	72,00
Gross Weight	Kg	85,00
Volume packed	m3	0,37

GAS FRY-TOP, FTG/C-710
 Made of stainless steel AISI-304 (18/10).
 Smooth hot-plate. Surface area: 43 dm².
 50 microns thickness chromium coated steel sheeting hot-plate.
 Burners in stainless steel with pilot.
 Thermostat control of the hot-plate temperature 120 C° -310 C°.
 Fat collector under the grill.
 Power: 12000 Kcal/h. (13.96 kW).
 Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	13,96
	Kcal/h	12.005,60
LPG		
Consumption (kg/h)		1,05
Pressure (g/cm ²)		37,00
Natural Gas		
Consumption (m ³ /h)		1,33
Pressure (g/cm ²)		18,00


Water

Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Certificate EQNET 99AR307

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	57	R.3/4"G





700 SERIES

GAS FRY-TOP, FTG-710 VL

1120201630

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	72,00
Gross Weight	Kg	85,00
Volume packed	m3	0,37

GAS FRY-TOP, FTG-710 VL
 Made of stainless steel AISI-304 (18/10).
 Smooth hot-plate. Surface area: 43 dm².
 Burners in stainless steel with pilot.
 Safety valves and thermocouples.
 Fat collector under the grill.
 Power: 12000 Kcal/h. (13.96 kW).
 Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas


Gas Power	KW	13,96
	Kcal/h	12.005,60
LPG		
Consumption (kg/h)		1,05
Pressure (g/cm ²)		37,00
Natural Gas		
Consumption (m ³ /h)		1,33
Pressure (g/cm ²)		18,00

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Certificate EQNET 99AR307

<u>Installation</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	57	R.3/4"G





700 SERIES

GAS FRY-TOP, FTG-710 VR

1120201632

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	72,00
Gross Weight	Kg	85,00
Volume packed	m3	0,37

GAS FRY-TOP, FTG-710 VR
 Made of stainless steel AISI-304 (18/10).
 Ribbed hot-plate. Surface area: 43 dm².
 Burners in stainless steel with pilot.
 Safety valves and thermocouples.
 Fat collector under the grill.
 Power: 12000 Kcal/h. (13.96 kW).
 Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas


Gas Power	KW	13,96
	Kcal/h	12.005,60
LPG		
Consumption (kg/h)		1,05
Pressure (g/cm ²)		37,00
Natural Gas		
Consumption (m ³ /h)		1,33
Pressure (g/cm ²)		18,00

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Certificate EQNET 99AR307

<u>Installation</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	57	R.3/4"G





700 SERIES

GAS FRY-TOP, FTG-710 V L+R

1120201634

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	72,00
Gross Weight	Kg	85,00
Volume packed	m3	0,37

GAS FRY-TOP, FTG-710 V L+R

Made of stainless steel AISI-304 (18/10).
 2/3 smooth + 1/3 ribbed hot-plate. Surface area: 43 dm².
 Burners in stainless steel with pilot.
 Safety valves and thermocouples.
 Fat collector under the grill.
 Power: 12000 Kcal/h. (13.96 kW).
 Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	13,96
	Kcal/h	12.005,60
LPG		
Consumption (kg/h)		1,05
Pressure (g/cm ²)		37,00
Natural Gas		
Consumption (m ³ /h)		1,33
Pressure (g/cm ²)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Certificate EQNET

99AR307

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	660	494	57	R.3/4"G





700 SERIES

GAS FRY-TOP, FTG-705 L

1120201900

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	43,00
Gross Weight	Kg	55,00
Volume packed	m3	0,19

GAS FRY-TOP, FTG-705 L

Made of stainless steel AISI-304 (18/10).
 Smooth hot-plate. Surface area: 21 dm².
 Burner in stainless steel with pilot.
 Thermostat control of the hot-plate temperature 120 C° -310 C°.
 Fat collector under the grill.
 Power: 6000 Kcal/h. (6.98 kW).
 Dimensions: 350 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	6,99
	Kcal/h	6.011,40
LPG		
Consumption (kg/h)		0,52
Pressure (g/cm ²)		37,00
Natural Gas		
Consumption (m ³ /h)		0,66
Pressure (g/cm ²)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Certificate EQNET

99AR307

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	310	494	57	R.3/4"G





700 SERIES

GAS FRY-TOP, FTG-705 R

1120201903

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	43,00
Gross Weight	Kg	55,00
Volume packed	m3	0,19

GAS FRY-TOP, FTG-705 R
 Made of stainless steel AISI-304 (18/10).
 Ribbed hot-plate. Surface area: 21 dm².
 Burner in stainless steel with pilot.
 Thermostat control of the hot-plate temperature 120 C° -310 C°.
 Fat collector under the grill.
 Power: 6000 Kcal/h. (6.98 kW).
 Dimensions: 350 x 750 x 290 mm.

Electricity

No

Gas


Gas Power	KW	6,99
	Kcal/h	6.011,40
LPG		
Consumption (kg/h)		0,52
Pressure (g/cm ²)		37,00
Natural Gas		
Consumption (m ³ /h)		0,66
Pressure (g/cm ²)		18,00

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Certificate EQNET 99AR307

<u>Installation</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	310	494	57	R.3/4"G





700 SERIES

GAS FRY-TOP, FTG/C-705

1120201906

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	43,00
Gross Weight	Kg	55,00
Volume packed	m3	0,19

GAS FRY-TOP, FTG/C-705

Made of stainless steel AISI-304 (18/10).
 Smooth hot-plate. Surface area: 21 dm².
 50 microns thickness chromium coated steel sheeting hot-plate.
 Burner in stainless steel with pilot.
 Thermostat control of the hot-plate temperature 120 C° -310 C°.
 Fat collector under the grill.
 Power: 6000 Kcal/h. (6.98 kW).
 Dimensions: 350 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	6,99
	Kcal/h	6.011,40
LPG		
Consumption (kg/h)		0,52
Pressure (g/cm ²)		37,00
Natural Gas		
Consumption (m ³ /h)		0,66
Pressure (g/cm ²)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Certificate EQNET

99AR307

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	310	494	57	R.3/4"G





700 SERIES

GAS FRY-TOP, FTG-705 VL

1120201925

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	43,00
Gross Weight	Kg	55,00
Volume packed	m3	0,19

GAS FRY-TOP, FTG-705 VL
 Made of stainless steel AISI-304 (18/10).
 Smooth hot-plate. Surface area: 21 dm².
 Burner in stainless steel with pilot.
 Safety valve and thermocouple.
 Fat collector under the grill.
 Power: 6000 Kcal/h. (6.98 kW).
 Dimensions: 350 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	6,99
	Kcal/h	6.011,40
LPG		
Consumption (kg/h)		0,52
Pressure (g/cm ²)		37,00
Natural Gas		
Consumption (m ³ /h)		0,66
Pressure (g/cm ²)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Certificate EQNET

99AR307

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	310	494	57	R.3/4"G





700 SERIES

GAS FRY-TOP, FTG-705 VR

1120201927

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	43,00
Gross Weight	Kg	55,00
Volume packed	m3	0,19

GAS FRY-TOP, FTG-705 VR
 Made of stainless steel AISI-304 (18/10).
 Ribbed hot-plate. Surface area: 21 dm².
 Burner in stainless steel with pilot.
 Safety valve and thermocouple.
 Fat collector under the grill.
 Power: 6000 Kcal/h. (6.98 kW).
 Dimensions: 350 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	6,99
	Kcal/h	6.011,40
LPG		
Consumption (kg/h)		0,52
Pressure (g/cm ²)		37,00
Natural Gas		
Consumption (m ³ /h)		0,66
Pressure (g/cm ²)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Certificate EQNET

99AR307

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	310	494	57	R.3/4"G





700 SERIES

ELECTRIC FRY-TOP, FTE-705 L

1120201700

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	43,00
Gross Weight	Kg	55,00
Volume packed	m3	0,19

ELECTRIC FRY-TOP, FTE-705 L
 Made of stainless steel AISI-304 (18/10).
 Smooth hot-plate. Surface area: 21 dm².
 Shielded elements in stainless steel for heating.
 Thermostat control of the hot-plate temperature 120 C° -310 C°.
 Fat collector under the grill.
 Power: 4.5 kW.
 Dimensions: 350 x 750 x 290 mm.

Electricity

Electric Power	KW	4,50
Voltage 230V -I+N		2x2,5+T - 25 A
Voltage 230V - III		3x1,5+T - 16 A
Voltage 400V - III+N		4x1,5+T - 10 A

Gas


No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	250	200	0	





700 SERIES

ELECTRIC FRY-TOP, FTE-705 R

1120201703

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	43,00
Gross Weight	Kg	55,00
Volume packed	m3	0,19

ELECTRIC FRY-TOP, FTE-705 R
 Made of stainless steel AISI-304 (18/10).
 Ribbed hot-plate. Surface area: 21 dm².
 Shielded elements in stainless steel for heating.
 Thermostat control of the hot-plate temperature 120 C° -310 C°.
 Fat collector under the grill.
 Power: 4.5 kW.
 Dimensions: 350 x 750 x 290 mm.

Electricity

Electric Power	KW	4,50
Voltage 230V -I+N		2x2,5+T - 25 A
Voltage 230V - III		3x1,5+T - 16 A
Voltage 400V - III+N		4x1,5+T - 10 A

Gas


No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	250	200	0	





700 SERIES

ELECTRIC FRY-TOP, FTE/C-705

1120201706

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	43,00
Gross Weight	Kg	55,00
Volume packed	m3	0,19

ELECTRIC FRY-TOP, FTE/C-705

Made of stainless steel AISI-304 (18/10).
 Smooth hot-plate. Surface area: 21 dm².
 50 microns thickness chromium coated steel sheeting hot-plate.
 Shielded elements in stainless steel for heating.
 Thermostat control of the hot-plate temperature 120 C° -310 C°.
 Fat collector under the grill.
 Power: 4.5 kW.
 Dimensions: 350 x 750 x 290 mm.

Electricity

Electric Power	KW	4,50
Voltage 230V -1+N		2x2,5+T - 25 A
Voltage 230V - III		3x1,5+T - 16 A
Voltage 400V - III+N		4x1,5+T - 10 A

Gas


No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	250	200	0	





700 SERIES

ELECTRIC FRY-TOP, FTE-710 L

1120201800

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	70,00
Gross Weight	Kg	81,00
Volume packed	m3	0,37

ELECTRIC FRY-TOP, FTE-710 L
 Made of stainless steel AISI-304 (18/10).
 Smooth hot-plate. Surface area: 43 dm².
 Shielded elements in stainless steel for heating.
 Thermostat control of the hot-plate temperature 120 C° -310 C°.
 Fat collector under the grill.
 Power: 9 kW.
 Dimensions: 700 x 750 x 290 mm.

Electricity

Electric Power	KW	9,00
Voltage 230V -I+N		2x10+T - 50 A
Voltage 230V - III		3x4+T - 32 A
Voltage 400V - III+N		4x1,5+T - 16 A

Gas


No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	600	200	0	





700 SERIES

ELECTRIC FRY-TOP, FTE-710 R

1120201803

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	70,00
Gross Weight	Kg	81,00
Volume packed	m3	0,37

ELECTRIC FRY-TOP, FTE-710 R

Made of stainless steel AISI-304 (18/10).
 Ribbed hot-plate. Surface area: 43 dm².
 Shielded elements in stainless steel for heating.
 Thermostat control of the hot-plate temperature 120 C° -310 C°.
 Fat collector under the grill.
 Power: 9 kW.
 Dimensions: 700 x 750 x 290 mm.

Electricity

Electric Power	KW	9,00
Voltage 230V -1+N		2x10+T - 50 A
Voltage 230V - III		3x4+T - 32 A
Voltage 400V - III+N		4x1,5+T - 16 A

Gas


No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	600	200	0	





700 SERIES

ELECTRIC FRY-TOP, FTE-710 L+R

1120201806

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	70,00
Gross Weight	Kg	81,00
Volume packed	m3	0,37

ELECTRIC FRY-TOP, FTE-710 L+R

Made of stainless steel AISI-304 (18/10).

½ smooth – ½ ribbed hot-plate. Surface area: 43 dm².

Shielded elements in stainless steel for heating.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fat collector under the grill.

Power: 9 kW.

Dimensions: 700 x 750 x 290 mm.

Electricity

Electric Power	KW	9,00
Voltage 230V - I+N		2x10+T - 50 A
Voltage 230V - III		3x4+T - 32 A
Voltage 400V - III+N		4x1,5+T - 16 A

Gas


No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	600	200	0	





700 SERIES

ELECTRIC FRY-TOP, FTE/C-710

1120201809

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	70,00
Gross Weight	Kg	81,00
Volume packed	m3	0,37

ELECTRIC FRY-TOP, FTE/C-710
 Made of stainless steel AISI-304 (18/10).
 Smooth hot-plate. Surface area: 43 dm².
 50 microns thickness chromium coated steel sheeting hot-plate.
 Shielded elements in stainless steel for heating.
 Thermostat control of the hot-plate temperature 120 C° -310 C°.
 Fat collector under the grill.
 Power: 9 kW.
 Dimensions: 700 x 750 x 290 mm.

Electricity

Electric Power	KW	9,00
Voltage 230V -1+N		2x10+T - 50 A
Voltage 230V - III		3x4+T - 32 A
Voltage 400V - III+N		4x1,5+T - 16 A

Gas


No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	600	200	0	





700 SERIES

GAS BOILING PAN, MG-710

1120511500

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	94,00
Gross Weight	Kg	120,00
Volume packed	m3	0,78

GAS BOILING PAN, MG-710

Made of stainless steel AISI-304 (18/10).

Capacity: 80 litres.

Counterweighted folding lid.

Stainless steel burner, with safety valve and thermocouple.

Piezoelectric ignition.

Cold and hot water filling tap.

Drainage tap.

Power: 15000 Kcal/h. (17.44 kW).

Dimensions: 700 x 750 x 850 mm.

Electricity

No

Gas

Gas Power	KW	17,44
	Kcal/h	14.998,40

LPG

Consumption (kg/h)	1,42
Pressure (g/cm2)	37,00

Natural Gas

Consumption (m3/h)	1,80
Pressure (g/cm2)	18,00


Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR282

<u>Installation</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
COLD WATER	528	700	105	1/2"
HOT WATER	468	700	105	1/2"
GAS	662	494	105	R.3/4"G





700 SERIES

GAS BOILING PAN, MG-710-BM

1120511600

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	94,00
Gross Weight	Kg	120,00
Volume packed	m3	0,78

GAS BOILING PAN, MG-710-BM

Made of stainless steel AISI-304 (18/10).

Capacity: 80 litres. Double jacket pan (bain-marie system).

Counterweighted folding lid.

Stainless steel burner, with safety valve and thermocouple.

Piezoelectric ignition.

Safety device for the bain-marie extinguishes the burner in the event of low water level.

Cold and hot water filling tap.

Drainage tap.

Filling tap and control tap for the level of the double jacket pan (bain-marie).

Over-pressure safety valve.

Power: 15000 Kcal/h. (17.44 kW).

Dimensions: 700 x 750 x 850 mm.

Electricity

No

Gas

Gas Power	KW	17,44
	Kcal/h	14.998,40
LPG		
Consumption (kg/h)		1,42
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		1,80
Pressure (g/cm2)		18,00


Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR282

<u>Installation</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
HOT WATER	468	700	105	1/2"
COLD WATER	528	700	105	1/2"
GAS	662	494	105	R.3/4"G





700 SERIES

ELECTRIC BOILING PAN, ME-710-BM

1120511700

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	94,00
Gross Weight	Kg	120,00
Volume packed	m3	0,78

Electricity

Electric Power	KW	9,00
Voltage 230V - I+N		2x10+T - 50 A
Voltage 230V - III		3x4+T - 32 A
Voltage 400V - III+N		4x1,5+T - 16 A

Gas

No

ELECTRIC BOILING PAN, ME-710-BM


Made of stainless steel AISI-304 (18/10).
 Capacity: 80 litres. Double jacket pan (bain-marie system).
 Counterweighted folding lid.
 Shielded heating elements in stainless steel.
 Pilot light for heating. Control by thermostat.
 Cold and hot water filling tap.
 Drainage tap.
 Filling tap and control tap for the level of the double jacket pan (bain-marie).
 Over-pressure safety vale.
 Power: 9 kW.
 Dimensions: 700 x 750 x 850 mm.

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	105	690	150	
COLD WATER	540	700	135	1/2"
HOT WATER	470	700	135	1/2"





700 SERIES

STEAM OPERATED BOILING PAN, MV-710 BM

1120514700

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	80,00
Gross Weight	Kg	90,00
Volume packed	m3	0,76

STEAM OPERATED BOILING PAN, MV-710 BM
 Made of stainless steel AISI-304 (18/10).
 Capacity: 80 litres.
 Double jacket pan (bain-marie system).
 Counterweighted folding lid.
 Pressure of inlet steam: 0,4 - 0,5 bar.
 1 " control knob for inlet steam in the bain marie system.
 Steam circulates inside the bain marie jacket pan.
 Outlet pipe for the condensed steam in the bottom of the pan.
 Water filling tap.
 Drainage tap.
 Over-pressure safety valve and manometer.
 Dimensions: 700 x 750 x 850 mm.

Electricity

No


Gas

No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

<u>Installation</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
COLD WATER	655	842	105	1/2"
DRAIN	425	800	105	1/2"
	805	635	105	





700 SERIES

GAS FRYER, FG-710

1120811300

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	57,00
Gross Weight	Kg	68,00
Volume packed	m3	0,35

GAS FRYER, FG-710

Made of stainless steel AISI-304 (18/10)

Capacity: one 15 litre oil/well.

Tank equipment: 1 basket 250x280 or 2 small baskets 250x135 mm .

Cast iron burners.

Thermostat temperature control 60 °C to 195 °C.

Automatic burner ignition by means of an electromagnetic valve, with pilot light and thermocouple. Safety thermostat.

Drainage tap.

Power: 13000 Kcal/h. (15.11 kW).

Dimensions: 350 x 750 x 850 mm.

Electricity

Electric Power	KW	0,05
Voltage 230V - I+N		2x1,5+T - 2 A
Voltage 230V - III		
Voltage 400V - III+N		

Gas

Gas Power	KW	15,11
	Kcal/h	12.994,60
LPG		
Consumption (kg/h)		1,25
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		1,59
Pressure (g/cm2)		18,00


Water

Consumption (lit/h)		0,00
Pressure (Kg/cm2)		

Certificate EQNET

99AR284

<u>Installation</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	286	540	150	
GAS	312	492	105	R.3/4"G





700 SERIES

ELECTRIC FRYER, FE-710

1120811402

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	57,00
Gross Weight	Kg	68,00
Volume packed	m3	0,35

ELECTRIC FRYER, FE-710

Made of stainless steel AISI-304 (18/10)

Capacity: one 15 litre oil/well.

Tank equipment: 1 basket 250x280 or 2 small baskets 250x135 mm .

Shielded heating elements in stainless steel.

Pilot light for heating. Control by thermostat (60 °C to 195 °C).

Safety thermostat. Drainage tap.

Power: 13.5 kW.

Dimensions: 350 x 750 x 850 mm.

Electricity

Electric Power	KW	13,50
Voltage 230V - I+N		2x16+T - 80 A
Voltage 230V - III		3x16+T - 40 A
Voltage 400V - III+N		4x2,66+T - 25 A

Gas


No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	264	618	650	





700 SERIES

GAS FRYER, FG-720

1120811500

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	104,00
Gross Weight	Kg	119,00
Volume packed	m3	0,66

GAS FRYER, FG-720

Made of stainless steel AISI-304 (18/10)

Capacity: two 15 litre oil/well.

Tank equipment: 1 basket 250x280 or 2 small baskets 250x135 mm .

Cast iron burners.

Thermostats temperature control 60 °C to 195 °C.

Automatic burner ignition by means of an electromagnetic valve, with pilot light and thermocouple. Safety thermostat.

Drainage taps.

Power: 26000 Kcal/h. (30.22 kW).

Dimensions: 700 x 750 x 850 mm.

Electricity

Electric Power	KW	0,05
Voltage 230V -1+N		2x1,5+T - 2 A
Voltage 230V - III		
Voltage 400V - III+N		

Gas

Gas Power	KW	30,22
	Kcal/h	25.989,20
LPG		
Consumption (kg/h)		2,50
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		3,18
Pressure (g/cm2)		18,00


Water

Consumption (lit/h)		0,00
Pressure (Kg/cm2)		

Certificate EQNET

99AR284

<u>Installation</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	636	540	150	
ELECTRICITY	286	540	150	
GAS	312	492	105	R.3/4"G
GAS	662	492	105	R.3/4"G





700 SERIES

ELECTRIC FRYER, FE-720

1120811602

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	104,00
Gross Weight	Kg	119,00
Volume packed	m3	0,66

ELECTRIC FRYER, FE-720

Made of stainless steel AISI-304 (18/10)
 Capacity: two 15 litre oil/well.
 Tank equipment: 1 basket 250x280 or 2 small baskets 250x135 mm .
 Shielded heating elements in stainless steel.
 Pilot light for heating. Control by thermostats
 (60 °C to 195 °C).
 Safety thermostats. Drainage taps.
 Power: 27 kW.
 Dimensions: 700 x 750 x 850 mm.

Electricity

Electric Power	KW	27,00
Voltage 230V -1+N		2x16+T - 80 A
Voltage 230V - III		3x16+T - 40 A
Voltage 400V - III+N		4x2,66+T - 25 A

Gas


No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	264	618	650	
ELECTRICITY	614	618	650	





700 SERIES

GAS TILTING BRATT PAN, SBG-710 I

1121122800

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	114,00
Gross Weight	Kg	149,00
Volume packed	m3	0,74

GAS TILTING BRATT PAN, SBG-710 I

Made of stainless steel AISI-304 (18/10)

Pan capacity: 50 litres (approx.). Surface area: 42 dm²

Stainless steel pan, with heat diffuser bottom 10 mm. thick. Crank raising system.

Counterweighted folding lid.

Stainless steel tubular burner controlled by solenoid valve and thermostat temperature control (50 °C to 315 °C).

Water filling tap.

Power: 12000 Kcal/h. (13.96 kW).

Dimensions: 700 x 750 x 850 mm.

Electricity

Electric Power	KW	0,05
Voltage 230V -1+N		2x1,5+T - 2 A
Voltage 230V - III		
Voltage 400V - III+N		

Gas

Gas Power	KW	13,96
	Kcal/h	12.005,60
LPG		
Consumption (kg/h)		1,09
Pressure (g/cm ²)		37,00
Natural Gas		
Consumption (m ³ /h)		1,38
Pressure (g/cm ²)		18,00


Water

Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Sound level (db)

Certificate EQNET 99AR308

<u>Installation</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	500	600	150	
COLD WATER	350	600	105	1/2"
GAS	662	494	105	R.3/4"G





700 SERIES

ELECTRIC TILTING BRATT PAN, SBE-710 I

1121122900

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	850,00
Net Weight	Kg	114,00
Gross Weight	Kg	149,00
Volume packed	m3	0,74

ELECTRIC TILTING BRATT PAN, SBE-710 I

Made of stainless steel AISI-304 (18/10)
 Pan capacity: 50 litres (approx.). Surface area: 42 dm²
 Stainless steel pan, with heat diffuser bottom 10 mm. thick.
 Counterweighted folding lid.
 Shielded elements controlled by thermostat. Pilot lights.
 Thermostat temperature control (50 °C to 315 °C).
 Water filling tap.
 Power: 9 kW.
 Dimensions: 700 x 750 x 850 mm.

Electricity

Electric Power	KW	9,00
Voltage 230V - I+N		2x10+T - 50 A
Voltage 230V - III		3x4+T - 32 A
Voltage 400V - III+N		4x1,5+T - 16 A

Gas

No


Water

Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Sound level (db)

Certificate EQNET

<u>Installation</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	500	600	150	
COLD WATER	350	600	105	1/2"





700 SERIES

GAS BAIN-MARIE, BMG-710

1121200600

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	34,00
Gross Weight	Kg	40,00
Volume packed	m3	0,32

GAS BAIN-MARIE, BMG-710

Made of stainless steel AISI-304 (18/10).
 Tank capacity: 30 litres.
 The tank is designed to accommodate GN containers.
 Built with separators for containers.
 Piezoelectric ignition and pilot. Safety thermocouple.
 Thermostat temperature control (30 °C to 90 °C)
 Water intake tap.
 Drainage with overflow.
 Power: 5500 Kcal/h. (6.40 kW).
 Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	6,40
	Kcal/h	5.504,00
LPG		
Consumption (kg/h)		0,54
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		0,69
Pressure (g/cm2)		18,00


Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET

99AR328

<u>Installation</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
DRAIN	38	199	0	30x25
COLD WATER	38	494	0	1/2"
GAS	662	494	50	R.3/4"G





700 SERIES

ELECTRIC BAIN-MARIE, BME-705

1121200800

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	21,00
Gross Weight	Kg	27,00
Volume packed	m3	0,17

ELECTRIC BAIN-MARIE, BME-705
 Made of stainless steel AISI-304 (18/10).
 Tank capacity: 17 litres.
 The tank is designed to accommodate GN containers.
 Built with separators for containers.
 Shielded elements controlled by thermostat. Pilot lights.
 Thermostat temperature control (30 °C to 90 °C)
 Water intake tap.
 Drainage with overflow.
 Power: 2800 W.
 Dimensions: 350 x 750 x 290 mm.

Electricity

Electric Power	KW	2,80
Voltage 230V -1+N	2x1,5+T - 16 A	
Voltage 230V - III		
Voltage 400V - III+N		


Gas

No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Installation	X	Y	Z	Diameters
ELECTRICITY	312	494	0	
DRAIN	38	199	0	30x25
COLD WATER	38	494	0	1/2"





700 SERIES

ELECTRIC BAIN-MARIE, BME-710

1121200900

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	34,00
Gross Weight	Kg	40,00
Volume packed	m3	0,32

ELECTRIC BAIN-MARIE, BME-710

Made of stainless steel AISI-304 (18/10).
 Tank capacity: 30 litres.
 The tank is designed to accommodate GN containers.
 Built with separators for containers.
 Shielded elements controlled by thermostat. Pilot lights.
 Thermostat temperature control (30 °C to 90 °C)
 Water intake tap.
 Drainage with overflow.
 Power: 6000 W
 Dimensions: 700 x 750 x 290 mm.

Electricity

Electric Power	KW	6,00
Voltage 230V -1+N		2x4+T - 32 A
Voltage 230V - III		3x2,5+T - 20 A
Voltage 400V - III+N		4x2,5+T - 16 A

Gas


No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Installation

	X	Y	Z	Diameters
ELECTRICITY	662	494	0	
DRAIN	38	199	0	30x25
COLD WATER	38	494	0	1/2"





700 SERIES

GAS PASTA COOKER, CPG-705

1121211450

Dimensions and Weights

Length	mm	350,00	GAS PASTA COOKER, CPG-705
Depth	mm	750,00	Made of stainless steel AISI-304 (18/10).
Height	mm	850,00	Cast iron burners.
Net Weight	Kg	60,00	Thermostat temperature control.
Gross Weight	Kg	76,00	Equipped with 3 small baskets.
Volume packed	m3	0,35	Water filling tap. Drainage tap.
			Capacity: 20 liters.
			Power: 12,000 kcal/h. (13.95 kW).
			Dimensions: 350 x 750 x 850 mm.

Electricity

No

Gas


Gas Power	KW	13,95
	Kcal/h	11.997,00
LPG		
Consumption (kg/h)		1,04
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		1,32
Pressure (g/cm2)		18,00

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
DRAIN	274	542	115	30x25
COLD WATER	45	448	115	1/2"
GAS	305	482	115	R.3/4"G





700 SERIES

ELECTRIC PASTA COOKER, CPE-705

1121226700

Dimensions and Weights

Length	mm	350,00	ELECTRIC PASTA COOKER, CPE-705
Depth	mm	750,00	Made of stainless steel AISI-304 (18/10).
Height	mm	850,00	Heater elements in stainless steel.
Net Weight	Kg	60,00	Thermostat temperature control.
Gross Weight	Kg	76,00	Equipped with 3 small baskets.
Volume packed	m3	0,39	Water filling tap. Drainage tap.
			Capacity: 30 liters.
			Power: 8 KW.
			Dimensions: 350 x 750 x 850 mm.

Electricity

Electric Power	KW	8,00
Voltage 230V -1+N		
Voltage 230V - III		
Voltage 400V - III+N	3x4+N+T	

Gas


No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	320	600	600	
DRAIN	274	542	115	30x25
COLD WATER	45	448	115	1/2"





700 SERIES

GAS CHARCOAL GRILL, BG-705 I

1130110000

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	40,00
Gross Weight	Kg	48,00
Volume packed	m3	0,20

GAS CHARCOAL GRILL, BG-705 I
 Made of stainless steel AISI-304 (18/10).
 Burner in stainless steel with pilot.
 Piezoelectric burner ignition. Safety valve and thermocouple.
 Lava rocks.
 Stainless steel grid. Grid dimensions: 340 x 500 mm.
 The angle of the cooking grid can be adjusted to three positions.
 Fat collector.
 Power: 6000 kcal/h (6.98 kW).
 Dimensions: 350 x 750 x 290 mm.

Electricity

No

Gas


Gas Power	KW	6,98
	Kcal/h	6.002,80
LPG		
Consumption (kg/h)		0,63
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		0,80
Pressure (g/cm2)		18,00

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Certificate EQNET 99AS392

<u>Installation</u>	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	310	485	132	R.3/4"G





700 SERIES

GAS CHARCOAL GRILL, BG-705

1130110070

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	40,00
Gross Weight	Kg	48,00
Volume packed	m3	0,20

GAS CHARCOAL GRILL, BG-705

Made of stainless steel AISI-304 (18/10).

Burner in stainless steel with pilot.

Piezoelectric burner ignition. Safety valve and thermocouple.

Lava rocks.

Cast iron grid. Grid dimensions: 340 x 500 mm.

The angle of the cooking grid can be adjusted to three positions.

Fat collector.

Power: 6000 kcal/h (6.98 kW).

Dimensions: 350 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	6,98
	Kcal/h	6.002,80
LPG		
Consumption (kg/h)		0,63
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		0,80
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Sound level (db)

Certificate EQNET 99AS392

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
GAS	310	485	132	R.3/4"G





700 SERIES

GAS CHARCOAL GRILL, BG-710 I

1130110100

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	65,00
Gross Weight	Kg	86,50
Volume packed	m3	0,37

GAS CHARCOAL GRILL, BG-710 I

Made of stainless steel AISI-304 (18/10).

Burner in stainless steel with pilot.

Piezoelectric burner ignition. Safety valve and thermocouple.

Lava rocks.

Two stainless steel grids.

Grid dimensions: 340 x 500 mm.

The angle of the cooking grid can be adjusted to three positions.

Fat collector.

Power: 12.000 kcal/h (13.96 kW).

Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	13,96
	Kcal/h	12.005,60
LPG	Consumption (kg/h)	1,26
	Pressure (g/cm ²)	37,00
	Natural Gas	
	Consumption (m ³ /h)	1,60
	Pressure (g/cm ²)	18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm ²)	

Certificate EQNET

99AS392

Installation

	X	Y	Z	Diameters
GAS	660	485	132	R.3/4"G





700 SERIES

GAS CHARCOAL GRILL, BG-710

1130110170

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	65,00
Gross Weight	Kg	86,50
Volume packed	m3	0,37

GAS CHARCOAL GRILL, BG-710

Made of stainless steel AISI-304 (18/10).

Burner in stainless steel with pilot.

Piezoelectric burner ignition. Safety valve and thermocouple.

Lava rocks.

One cast iron grid and one stainless steel grid.

Grid dimensions: 340 x 500 mm.

The angle of the cooking grid can be adjusted to three positions.

Fat collector.

Power: 12.000 kcal/h (13.96 kW).

Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas

Gas Power	KW	13,96
	Kcal/h	12.005,60
LPG		
Consumption (kg/h)		1,26
Pressure (g/cm2)		37,00
Natural Gas		
Consumption (m3/h)		1,60
Pressure (g/cm2)		18,00

Water


Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Sound level (db)

Certificate EQNET 99AS392

Installation

	X	Y	Z	Diameters
GAS	660	485	132	R.3/4"G





700 SERIES

WORK TOP, EN-705

1110102700

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	20,00
Gross Weight	Kg	25,00
Volume packed	m3	0,17

WORK TOP, EN-705

Made of stainless steel AISI-304 (18/10).
Removable top for cleaning purposes.
Dimensions: 350 x 750 x 290 mm.

Electricity

No

Gas

No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Sound level (db)

Certificate EQNET


Installation

X

Y

Z

Diameters





700 SERIES

WORK TOP, EN-710

1110102800

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	290,00
Net Weight	Kg	29,00
Gross Weight	Kg	43,00
Volume packed	m3	0,33

WORK TOP, EN-710

Made of stainless steel AISI-304 (18/10).
Removable top for cleaning purposes.
Dimensions: 700 x 750 x 290 mm.

Electricity

No

Gas

No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Sound level (db)

Certificate EQNET


Installation

X

Y

Z

Diameters





700 SERIES

STAND, MB-705

1121701000

Dimensions and Weights

Length	mm	350,00
Depth	mm	750,00
Height	mm	560,00
Net Weight	Kg	7,00
Gross Weight	Kg	11,00
Volume packed	m3	0,21

STAND, MB-705

Made of stainless steel AISI-304 (18/10).

Element for adding to the table-top appliances of Range 700 to obtain a compact unit.

Dimensions: 350 x 750 x 560 mm.

* Doors are available as an option

Electricity

No

Gas

No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Sound level (db)

Certificate EQNET


Installation

X

Y

Z

Diameters





700 SERIES

STAND, MB-710

1121702000

Dimensions and Weights

Length	mm	700,00
Depth	mm	750,00
Height	mm	560,00
Net Weight	Kg	9,00
Gross Weight	Kg	14,00
Volume packed	m3	0,37

STAND, MB-710

Made of stainless steel AISI-304 (18/10).

Element for adding to the table-top appliances of Range 700 to obtain a compact unit.

Dimensions: 700 x 750 x 290 mm.

* Doors are available as an option

Electricity

No

Gas

No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Sound level (db)

Certificate EQNET


Installation

X

Y

Z

Diameters





700 SERIES

STAND, MB-715

1121703000

Dimensions and Weights

Length	mm	1.050,00
Depth	mm	750,00
Height	mm	560,00
Net Weight	Kg	35,00
Gross Weight	Kg	40,00
Volume packed	m3	0,70

STAND, MB-715

Made of stainless steel AISI-304 (18/10).
 Element for adding to the table-top appliances of Range 700 to obtain a compact unit of 1.5 modules.
 Dimensions: 1,050 x 750 x 290 mm.

* Doors are available as an option

Electricity

No

Gas

No

Water

Consumption (lit/h)	0,00
Pressure (Kg/cm2)	

Installation

X

Y

Z

Diameters

