



Catalogue
CATERING
Chapter
REFRIGERATION

Model
 EAFP-1602/2 230V 1N 50Hz

19042473

04/04/2019

REFRIGERATED CABINET DE DOS TEMPERATURAS CONCEPT, EAFP-1602/2

- Constructed in AISI-304 stainless steel.
- Copper piping and aluminium flaps evaporator.
- Digital display for electronic and digital control of temperature and defrosting.
- Opened door delay alarm.
- Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
- Built-in drainage to get rid of waste liquids inside the unit.
- Embedded bottom and curved panels inside for easy cleaning and maintenance.
- Height adjustable stainless steel legs.
- Inner LED lights with power switch.
- 60 mm, 40 kg/m³ injected polyurethane insulation.
- Embedded inner tray slides. Storage trays at 24 different levels 55 mm from each other.
- Forced draught cooling system with hermetically sealed compressor.
- Removable plastic covered steel grid shelves for easy cleaning. Equipment: 3 shelves per large door.
- Working temperature: from -2 °C to +8 °C. Ambient temperature: 43 °C (Except specific intensive usage).
- Number of doors: 2

TWO TEMPERATURES:


- 2 separate compartments with independent refrigeration units, systems and thermostats.

Options:

- Locks.
- Castor kit (factory assembly).
- Tropicalised unit.
- HACCP.
- Door opening pedal (factory assembly).
- "- Stainless steel back panel.
- "

DIMENSIONS

X Width	1388 mm	X Gross width	1430 mm
Y Depth	826 mm	Y Gross depth	880 mm
Z Height	2008 mm	Z Gross height	2027 mm
Net Weight	302,0 kg	Gross Weight	320,0 kg
Net volume	2,302 m ³	Gross volume	2,551 m ³



ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,369 kW
Voltage	230V - 1N
Amperage	0,9
Electric frequency	50Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-600a
----------	--------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,296 kW
Annual elec. consumption	905,00 kWh
Power consumption 24h	2,48 kWh
Gross internal volume	1301 L
Refrigeration net.vol	437 L
Climate class	4
Cooling gas load	98,000 g
Clasif. Energy efficiency	D

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T-2A
--------------------------	------------



Catalogue
CATERING

Chapter
REFRIGERATION

Model
EAFP-1602/2 230V 1N 50Hz

19042473

04/04/2019

