



**Catalogue**  
**CATERING**  
**Chapter**  
**REFRIGERATION**

**Model**  
 EAFP-1604/2 230V 1N 50Hz

19042471

04/04/2019

**REFRIGERATED CABINET DE DOS TEMPERATURAS CONCEPT, EAFP-1604/2**

- Constructed in AISI-304 stainless steel.
  - Copper piping and aluminium flaps evaporator.
  - Digital display for electronic and digital control of temperature and defrosting.
  - Opened door delay alarm.
  - Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
  - Built-in drainage to get rid of waste liquids inside the unit.
  - Embedded bottom and curved panels inside for easy cleaning and maintenance.
  - Height adjustable stainless steel legs.
  - Inner LED lights with power switch.
  - 60 mm, 40 kg/m3 injected polyurethane insulation.
  - Embedded inner tray slides. Storage trays at 24 different levels 55 mm from each other.
  - Forced draught cooling system with hermetically sealed compressor.
  - Removable plastic covered steel grid shelves for easy cleaning.
- Equipment: 3 shelves per large door.
- Working temperature: from -2 °C to +8 °C. Ambient temperature: 43 °C (Except specific intensive usage).
  - Number of doors: 4

**TWO TEMPERATURES:**


- 2 separate compartments with independent refrigeration units, systems and thermostats.

**Options:**

- Castor kit (factory assembly).
- Tropicalised unit.
- HACCP.
- "- Stainless steel back panel.
- "

**DIMENSIONS**

X Width	1388 mm	X Gross width	1430 mm
Y Depth	826 mm	Y Gross depth	880 mm
Z Height	2008 mm	Z Gross height	2027 mm
Net Weight	302,0 kg	Gross Weight	320,0 kg
Net volume	2,302 m3	Gross volume	2,551 m3



**ELECTRICITY TECHNICAL SPECIFICATIONS**

Electric power	0,369 kW
Voltage	230V - 1N
Amperage	0,9
Electric frequency	50Hz

**GAS TECHNICAL SPECIFICATIONS**

Gas type	R-600a
----------	--------

**COLD TECHNICAL SPECIFICATIONS**

Refrigeration power	0,296 kW
Annual elec. consumption	905,00 kWh
Power consumption 24h	2,48 kWh
Gross internal volume	1301 L
Refrigeration net.vol	437 L
Climate class	4
Cooling gas load	98,000 g
Clasif. Energy efficiency	D

**CONNECTIONS TECHNICAL SPECIFICATIONS**

Single-phase 230V wiring	2X1,5+T-2A
--------------------------	------------



Catalogue  
**CATERING**

Chapter  
**REFRIGERATION**

Model  
**EAFP-1604/2 230V 1N 50Hz**

19042471

04/04/2019

