



Catalogue
CATERING
Chapter
REFRIGERATION

Model
 EAFP-802/2 230V 1N 50Hz

19042469

04/04/2019

REFRIGERATED CABINET DE DOS TEMPERATURAS CONCEPT, EAFP-802/2

- Constructed in AISI-304 stainless steel.
 - Copper piping and aluminium flaps evaporator.
 - Digital display for electronic and digital control of temperature and defrosting.
 - Opened door delay alarm.
 - Self-closing and stay open doors. When opened less than 90° they close by themselves. When opened more than 135° they stay open.
 - Built-in drainage to get rid of waste liquids inside the unit.
 - Embedded bottom and curved panels inside for easy cleaning and maintenance.
 - Height adjustable stainless steel legs.
 - Inner LED lights with power switch.
 - 60 mm, 40 kg/m3 injected polyurethane insulation.
 - Embedded inner tray slides. Storage trays at 24 different levels 55 mm from each other.
 - Forced draught cooling system with hermetically sealed compressor.
 - Removable plastic covered steel grid shelves for easy cleaning.
- Equipment: 3 shelves per large door.
- Working temperature: from -2 °C to +8 °C. Ambient temperature: 43 °C (Except specific intensive usage).
 - Number of doors: 2

TWO TEMPERATURES:


- 2 separate compartments with independent refrigeration units, systems and thermostats.

Options:

- Castor kit (factory assembly).
- Tropicalised unit.
- HACCP.
- "- Stainless steel back panel.
- "

DIMENSIONS

X Width	693 mm	X Gross width	730 mm
Y Depth	826 mm	Y Gross depth	880 mm
Z Height	2008 mm	Z Gross height	2027 mm
Net Weight	167,0 kg	Gross Weight	175,0 kg
Net volume	1,149 m3	Gross volume	1,302 m3



ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,502 kW
Voltage	230V - 1N
Amperage	2,5 A
Electric frequency	50Hz

GAS TECHNICAL SPECIFICATIONS

Gas type	R-290
----------	-------

COLD TECHNICAL SPECIFICATIONS

Refrigeration power	0,250 kW
Annual elec. consumption	679,00 kWh
Power consumption 24h	1,86 kWh
Gross internal volume	596 L
Refrigeration net.vol	218 L
Climate class	4
Cooling gas load	98,000 g
Clasif. Energy efficiency	D

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 4 A
--------------------------	---------------



Catalogue
CATERING

Chapter
REFRIGERATION

Model
EAFP-802/2 230V 1N 50Hz

19042469

04/04/2019

